







A Compact and Affordable Duplex Scanner



















Features:


- AD340G scans 40 ppm/80ipm (at A4, Color, 300 dpi)
- Easy to carry due to the slim design
- Support embossed plastic cards
- Ultrasonic multi-feed detection
- Professional bundled software applications include Avision Button Manager V2, AVScan X, PaperPort SE 14
- Earth-friendly LED technology
- Compact ADF holds up to 50 pages
- Press and scan to cloud servers such as Google Drive, FTP, Evernote, and Microsoft SharePoint via Button Manager V2
- Latest USB3.2 Gen 1x1connectivity for faster transmission speed

Overview

The AD340G is a 40 ppm/80 ipm, duplex sheetfed scanner that is fast, reliable, and affordable for business where scanning plastic ID cards, business cards, documents or other heavy card stock is necessary. Embedded with Avision-developed image processor, the scanned image can be automatically cropped, straightened, and optimized with enhanced speed.

Ultrasonic multi-feed detection

With the built-in ultrasonic multi-feed detection capability, the scanner allows you to set overlapped paper by detecting paperthickness between document. When multi-feed is detected a warning message will be prompted.



High optical resolution of 600 dpi

With a high optical resolution of 600 dpi and advanced image processing technology, you can be assured documents can be converted in the highest image quality. In addition, with the build-in CIS (Contact Image Sensor) module, the AD340G does not require any warm-up time.

Color, and graphical LCD display

The AD340G is easy to use through the LCD display and buttons on the panel.

By selecting your destination and pressing the "Scan" button, the scan can be done and the scanned image can be sent to your specified destination application such as e-mail, printer,



or your favorable image-editing software application. Up to nine frequently used scan settings and destinations can be preset for different scanning needs.

AD340G saves your space when not in use

Both the input and output paper tray of the AD340G can be folded when not in use. This



feature not only helps prevent the unit from dust but also save more working space.

What we have bundled

The AD340G comes with TWAIN and ISIS drivers, and are bundled with a suite of powerful software applications that include Avision Button Manager V2, AVScan X and Nuance PaperPort SE 14.

Avision | AD340G Sheetfed Scanner

Avision's Button Manager V2

-Completes your scan with a single step





The Button Manager V2 main screen

Button Manager V2 makes it easy for you to scan and send your image to your favorite destinations with a press one button. Now the new version comes with an innovative feature to let you scan and automatically upload the scanned document to popular cloud repositories such as Google Docs, Microsoft SharePoint, or FTP. In addition, the iScan feature allows you to insert the scanned image or recognized text after optional OCR (Optical Character Recognition) process to your text editor such as Microsoft Word to get your job done easily and quickly.

AVScan X

-The Intelligent Document Management Tool



The AVScan X main screen

Document Imaging is the very first step of Document Management. However, poor quality images can cause serious problems to later indexing or storing processes. It may increase scanning labor costs and lowers the OCR accuracy. AVScan X ensures all documents are checked and polished at the time they are scanned such that the image quality is guaranteed before they are ready to use for other purposes.

AVScan X is an intelligent scanning and electronic filing solution. AVScan X possesses distinct features that convert and index scanned information into electronic documents for easy storage and fast retrieval.

Nuance PaperPort SE14

- The Professional Choice to Organize and Share Your Documents



The PaperPort SE14 main screen

PaperPort SE 14 is Nuance's most popular scanning and document management solution, carefully designed specifically for home office use. Part traditional file cabinet, part digital-document desktop, PaperPort SE 14 is the fastest and easiest way to scan, share, search and organize your documents. Additionally, PaperPort SE 14 now delivers anytime-anywhere access to your most important files however it's convenient for you – using a PC, Mac, iPhone, iPad, or Android device.

















Avision AD340G Product Specifications

Scanning Technology:Contact Image Sensor (CIS)Light Sourcce:LEDID card thickness:Up to 1.25 mmLong Page Mode:200 dpi: 6096 mm (240 in.)300 dpi: 5540 mm (218 in.)600 dpi: 1500 mm (59 in.)Scanning Size:Max. 216 x 356 mm (Legal) (8.5 x 14 in)Min. 74 x 52 mm (2.9 x 2.0 in)Scanning Speed:40 PPM/80 IPM (color, A4, 300 dpi)Paper Thickness:27-413 g/m² (7- 110 lb)Optical Resolution:600 dpiOutput Resolution:75, 100, 150, 200, 300, 400, 600, 1200 dpiHalftone Patterns:Dither and Error DiffusionGrayscale mode:16-bit input 8-bit outputColor mode:48-bit input 24-bit outputFile Formats:BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML.Bundled Software:Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14Interface/Drivers:USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash)Power Supply:Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5APower Consumption:Operation: 17WSleep: 1.9 W Ready: 6W Off: 0.2 WEnvironmental Factors:Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85%Acoustic Noise:Standby: <25 dB Operating: <52 dBMaximum (WxDxH):282 x 457 x 334 mmMinimum (WxDxH):282 x 152 x 165 mm	Paper Feeding:	ADF 50-page capacity
Light Source: LED D card thickness: Up to 1.25 mm		,
D card thickness: Up to 1.25 mm		9
Long Page Mode: 200 dpi: 6096 mm (240 in.) 300 dpi: 5540 mm (218 in.) 600 dpi: 1500 mm (59 in.) Scanning Size: Max. 216 x 356 mm (Legal) (8.5 x 14 in) Min. 74 x 52 mm (2.9 x 2.0 in) Scanning Speed: 40 PPM/80 IPM (color, A4, 300 dpi) Paper Thickness: 27-413 g/m² (7- 110 lb) Optical Resolution: 600 dpi Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, TTT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		
300 dpi: 5540 mm (218 in.)		<u> </u>
Scanning Size: Max. 216 x 356 mm (Legal) (8.5 x 14 in) Min. 74 x 52 mm (2.9 x 2.0 in)	Long Page Mode:	
Scanning Size: Max. 216 x 356 mm (Legal) (8.5 x 14 in) Min. 74 x 52 mm (2.9 x 2.0 in) Scanning Speed: 40 PPM/80 IPM (color, A4, 300 dpi) Paper Thickness: 27-413 g/m² (7-110 lb) Optical Resolution: 600 dpi Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: 225 dB Operating: <52 dB		. , ,
Min. 74 x 52 mm (2.9 x 2.0 in) Scanning Speed: 40 PPM/80 IPM (color, A4, 300 dpi) Paper Thickness: 27-413 g/m² (7-110 lb) Optical Resolution: 600 dpi Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Operation: 17W Power Consumption: Operation: 17W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB	C . C.	•
Scanning Speed: 40 PPM/80 IPM (color, A4, 300 dpi) Paper Thickness: 27-413 g/m² (7- 110 lb) Optical Resolution: 600 dpi Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB	Scanning Size:	3
Paper Thickness: 27-413 g/m² (7~110 lb) Optical Resolution: 600 dpi Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 152 x 165 mm		
Optical Resolution: 600 dpi Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 152 x 165 mm		. , , , , ,
Output Resolution: 75, 100, 150, 200, 300, 400, 600, 1200 dpi Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, TTF, TXPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 152 x 165 mm		
Halftone Patterns: Dither and Error Diffusion Grayscale mode: 16-bit input 8-bit output Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Poeration: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		•
Grayscale mode: Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: Operation: Neady: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		- · · · · · · · · · · · · · · · · · · ·
Color mode: 48-bit input 24-bit output File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		
File Formats: BMP, PNG, GIF, JPEG, PDF, Searchable PDF Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: Ready: Operation? W Sleep: 1.9 W Ready: Operation? W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		16-bit input 8-bit output
Multi-Page TIFF, TIFF, RTF, TXT, XPS, DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		
DOC, XLŠ, PPT, DOCX, XLSX, PPTX, HTML. Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm	File Formats:	
Bundled Software: Avision Button Manager V2, Avision AVScan X Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		Multi-Page TIFF, TIFF, RTF, TXT, XPS,
Nuance PaperPort SE 14 Interface/Drivers: USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: Sleep: 1.9 W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB		DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML.
Interface/Drivers: USB3.2 Gen 1x1 / USB 2.0 (Scan to Flash) Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: Sleep: 1.9 W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB	Bundled Software:	Avision Button Manager V2, Avision AVScan X
Power Supply: Input: 100~240 VAC, 50/60 Hz Output: 24V, 1.5A Power Consumption: Operation: 17W Sleep: 1.9 W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB		Nuance PaperPort SE 14
Output: 24V, 1.5A Power Consumption: Operation: 17W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB	Interface/Drivers:	USB3.2 Gen 1x1 /USB 2.0 (Scan to Flash)
Power Consumption: Operation: 17W Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB	Power Supply:	Input: 100~240 VAC, 50/60 Hz
Ready: 6W Off: 0.2 W Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB		Output: 24V, 1.5A
Environmental Factors: Operating temperature: 10°C to 35°C (50°F to 95°F) Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm	Power Consumption:	Operation: 17W Sleep: 1.9 W
Operating humidity: 10% to 85% Acoustic Noise: Standby: <25 dB Operating: <52 dB		Ready: 6W Off: 0.2 W
Acoustic Noise: Standby: <25 dB Operating: <52 dB	Environmental Factors:	Operating temperature: 10°C to 35°C (50°F to 95°F)
Maximum (WxDxH): 282 x 457 x 334 mm Minimum (WxDxH): 282 x 152 x 165 mm		Operating humidity: 10% to 85%
Minimum (WxDxH): 282 x 152 x 165 mm	Acoustic Noise:	Standby: <25 dB Operating: <52 dB
, , ,	Maximum (WxDxH):	282 x 457 x 334 mm
	Minimum (WxDxH):	282 x 152 x 165 mm
Weight: 2.5 kg	Weight:	2.5 kg
Recommended Daily up to 8,000 Sheets	Recommended Daily	up to 8,000 Sheets
Duty Cycle:	Duty Cycle:	
Multi-feed Detection: Ultrasonic Sensor	Multi-feed Detection:	Ultrasonic Sensor

We have endeaword to ensure that the information in this manual is a caratae and that Avision is too repostable for propagabilical errors. The above confined we actual configuration (software hardware) should be complied with the specification described in the purchase a greenent.

Avision inc. owns the intellectual properly right of the product voltock and design and the product outlook and design are subject to change. Avision reserves the if intellectual progressively report outlook and design and the product outlook and design are subject to change. Avision reserves the if intellectual products of the product outlook and design and the product outlook and design are subject to change. Avision reserves the if intellectual products only and whistin design are written the products not it responsible for the efficiency or use of these products.

System Requirements

4GB (64bit Windows) 4GB (64bit Windows) DVD-ROM: DVD ROM Drive USB: USB3.2 Gen 1x1 Windows' Operating System: Windows' 10, 8, 7 Contents Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X -Nuance PaperPort SE 14	tel [*] Core i3 (2.1GHz) or Higher y: 2GB (32ibit Windows)
DVD-ROM: DVD ROM Drive USB: USB3.2 Gen 1x1 Windows' Operating System: Windows' 10, 8, 7 Contents Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes:Scanner Driver (TWAIN/ISIS Driver)Avision Button Manager V2Avision AVScan X	
USB: USB3.2 Gen 1x1 Windows' Operating System: Windows' 10, 8, 7 Contents Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes:Scanner Driver (TWAIN/ISIS Driver)Avision Button Manager V2Avision AVScan X	. ,
Windows Operating System: Windows 10, 8, 7 Contents Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	
Windows 10, 8, 7 Contents Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes:Scanner Driver (TWAIN/ISIS Driver)Avision Button Manager V2Avision AVScan X	
Contents Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	
Scanner Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	15 10, 0, 7
Power Supply Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	ts
Quick Guide USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	·
USB3.2 Gen 1x1 Cable CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	
CD-ROM includes: -Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	
-Scanner Driver (TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	
(TWAIN/ISIS Driver) -Avision Button Manager V2 -Avision AVScan X	И includes:
-Avision Button Manager V2 -Avision AVScan X	ner Driver
-Avision AVScan X	IN/ISIS Driver)
-Nuance PaperPort SE 14	on AVScan X
	ce PaperPort SE 14



Specifications subject to change without notice.